



E-CODER®
SOLID STATE ABSOLUTE ENCODER



The E-Coder® is Neptune’s high-resolution solid state absolute encoder register. The E-Coder features a custom integrated-circuit design that digitally encodes the rotation of the measuring chamber, providing “absolute” registration with no internal battery requirement. The E-Coder functions in two modes: E-Coder BASIC and E-CoderPLUS. The E-Coder BASIC mode functionality is the same as ProRead™ (ARB® VI), featuring programmability up to a 10-digit ID number, three user characters, and 3-6 digit meter reading. In addition to the meter reading, the E-Coder provides a visual readout on rate of flow every twelve seconds when the LCD display is activated. When connected to Neptune’s R900® or R450™ radio frequency MIUs, the E-Coder automatically operates in E-CoderPLUS mode, providing a high-resolution, 8-digit remote meter reading, and value-added features including leak, tamper, and reverse flow detection. True point-of-use leak detection is provided by monitoring a 24-hour period in fifteen-minute intervals. Tamper detection is provided by reverse flow detection and monitoring the number of days of zero flow over the previous 35 days.

The E-CoderPLUS features are communicated through the E-Coder protocol, allowing host software platforms to interpret the data and pass the information directly to billing packages, CIS screens, and operational and maintenance reports. The E-CoderPLUS features enhance customer service and improve operational efficiencies for water utilities.

The E-Coder is available in two different configurations – inside set meters and pit set meters. For inside set applications, the E-Coder is housed in our plastic encoder register housing with terminal screws. For pit set applications, the E-Coder is housed in a glass lens and copper can enclosure with factory-potted wire connections.

KEY FEATURES

- “Absolute” 9-digit meter reading on display
- Up to 8-digit remote meter reading
- Battery-free functionality
- Pit set version: roll-sealed copper shell and glass lens
- Inside set version: plastic enclosure
- True point-of-use leak detection*
- Tamper detection*
- Reverse flow detection*
- LCD leak indicators
- Directional flow indicator
- Rate of flow on LCD display

KEY BENEFITS

- Enhanced “customer care”
 - Leak history/diagnostics
 - Proactive leak notification
- Increased operational efficiencies
 - Work order reduction for high water bill inquiries
 - Prioritization of meter maintenance
 - Drought management
 - Reduction of water loss through proactive notification of water leaks
- Tamper management
 - Identification and prioritization of potential tamper situations




** When connected to Neptune R900 or R450 RF MIUs.*

WARRANTY

Neptune provides a 10-year limited warranty with respect to its E-Coder solid state absolute encoder register for performance, materials, and workmanship.



- Solar Panel **1**
 Date of Manufacture **2**
 LCD Display **3**

	<p>FLOW INDICATOR Shows the direction of flow through the meter: ON Water in use. OFF Water not in use. Flashing Water is running slowly. (-) Reverse flow. (+) Forward flow.</p>
	<p>LEAK INDICATOR Displays a possible leak: OFF No leak indicated. Flashing Intermittent leak indicates that water has been used for at least 50 of the 96 15-minute intervals during the previous 24-hour period. On Continuously Indicates water use for all 96 15-minute intervals during the previous 24-hour period.</p>
<p>RATE</p>	<p>RATE OF FLOW Average flow rate is displayed every twelve (12) seconds on LCD display.</p>
	<p>LCD DISPLAY Nine-digit LCD displays the meter reading in billing units of measure: U.S. gallons, cubic feet, Imperial gallons, or cubic metres.</p> <p>1 E-Coder Basic Reading/Customary 6-digit remote reading 2 Customary sweep hand digits 3 E-CoderPLUS Reading (8-digit remote reading)</p>

- **Materials**
 - Inside Set Housing: polycarbonate
 - Pit Set Housing: copper shell and glass lens
 - Connecting wire: 3-lead #22 AWG
 - Remote receptacles: ABS, nylon, and polycarbonate
- **Distance**
 - A single register may be located with up to 500 feet (152 m) of wire from receptacle or MIU.
 - Two networked registers can be located with up to 300 feet (91m) of wire from receptacle or MIU.
- **Environmental Conditions**
 - Operating temperature: 15°F to 149°F (-10°C to 65°C)
 - Storage temperature: -40°F to 158°F (-40°C to 70°C)
 - Operating humidity: 0 to 100% (pit version)
- **Register**
 - Warranty: 10 years

- **Sizes**
 - Available for all sizes and makes of current Neptune meters
- **Electronic Accessory Equipment**
 - R900 Wall and Pit RF MIUs
 - R450 Wall and Pit RF MIUs
- **Data Collection Systems**
 - Pocket ProReader
 - Advantage
 - CE5320
 - MRX920™
 - R900® Gateways
- **Units of Measure**
 - US Gallons, Cubic Feet, Imperial Gallons, Cubic Metres
- 9-digit local registration
- 8-digit remote registration
- 4-8 digits can be communicated for billing

Neptune Technology Group Inc.
 1600 Alabama Highway 229
 Tallahassee, AL 36078
 USA
 Tel: (800) 633-8754
 Fax: (334) 283-7293

Neptune Technology Group (Canada) Ltd.
 7275 West Credit Avenue
 Mississauga, Ontario
 L5N 5M9
 Canada
 Tel: (905) 858-4211
 Fax: (905) 858-0428

Neptune Technology Group Inc.
 Ejército Nacional No. 418
 Piso 12, Desp. 1201-1202
 Col. Chapultepec Morales
 Delegación Miguel Hidalgo
 11570 México, Distrito Federal
 Tel: (525) 55203 5294 / (525) 55203 5708
 Fax: (525) 55203 6503

 **NEPTUNE**
 TECHNOLOGY GROUP
 neptunetg.com